

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
19 February 2004 (19.02.2004)

PCT

(10) International Publication Number
WO 2004/015350 A1

- (51) International Patent Classification⁷: **F28D 1/053**
- (21) International Application Number:
PCT/JP2003/010196
- (22) International Filing Date: 11 August 2003 (11.08.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
2002-232854 9 August 2002 (09.08.2002) JP
60/404,127 19 August 2002 (19.08.2002) US
- (71) Applicant (for all designated States except US): **SHOWA DENKO K.K.** [JP/JP]; 13-9, Shiba Daimon 1-chome, Minato-ku, Tokyo 105-8518 (JP).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **TERADA, Takashi** [JP/JP]; c/o SHOWA DENKO K.K., OYAMA REGIONAL OFFICE, 480, Inuzuka 1-chome, Oyama-shi, Tochigi 323-8678 (JP).
- (74) Agents: **HIBI, Norihiko et al.**; c/o KISHIMOTO & CO., 3rd Floor, Inaba Building, 13-18, Nishishinsaibashi 1-chome, Chuo-ku, Osaka-shi, Osaka 542-0086 (JP).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **FLAT TUBE AND PROCESS FOR PRODUCING HEAT EXCHANGER WITH USE OF THE FLAT TUBE**



(57) **Abstract:** A flat tube 1 comprises an upper wall 2, a lower wall 3, left and right side walls 4, 5 interconnecting the upper and lower walls 2, 3 at respective left and right side edges thereof, and a plurality of reinforcing walls 6 interconnecting the upper and lower walls 2, 3 and positioned between the left and right side walls 4, 5. The tube 1 has parallel fluid channels 7 inside thereof, and each of the reinforcing walls 6 has communication holes 8 for holding the adjacent fluid channels 7 in communication with each other therethrough. The reinforcing wall 6 is formed from a downward ridge 11 integral with the upper wall 2 and an upward ridge 12 integral with the lower wall 3, by brazing the two ridges to each other. Only one of the downward ridge 11 and the upward ridge 12 forming the reinforcing wall 6 is provided with a plurality of cutouts 13, 14. The openings of the cutouts 13, 14 are closed with the other ridge 11, 12 having no cutouts to thereby form the communication holes 8. The ridges 11, 12 forming the reinforcing wall 6 are brazed with an enhanced strength.